




TANDBERG
1000
 For Cisco® CallManager

The TANDBERG 1000 for Cisco CallManager provides the ultimate visual communications experience as a fully integrated part of the Cisco IP telephony environment. The features of Cisco CallManager, such as forward, transfer and hold are supported. Video is no longer just as easy as a phone call - it is a phone call.



DESIGN FEATURES

- Designed for small meeting rooms and executive offices in Cisco CallManager environments
- Completely integrated system including camera, 12.1" LCD screen, speakers, microphone and cables
- Ultra thin portable frame with optional wall bracket

APPLICATION FEATURES

- Full range of Cisco IP telephony functions, including Directory, Voice Mail and Call Control, as supported by Cisco CallManager
- Software upgradeable, to grow with the capabilities of Cisco CallManager
- Supports XML applications which deliver a range of information services to the desktop
- Interoperable with H.323 video conferencing, using Cisco CallManager
- Interoperable with H.320 (ISDN) video conferencing, using an H.323/H.320 video gateway and Cisco CallManager

PERFORMANCE FEATURES

- Bandwidth up to 768 kbps
- PC card slot for wireless LAN connection

SYSTEM COMPONENTS

Wireless remote control, built-in camera, microphone, speakers, cables, 12.1" LCD screen, table-top stand and optional wall mount bracket

LCD SCREEN

Wide view angle screen
SVGA resolution
Auto or manual brightness

BANDWIDTH

Cisco SCCP up to 768 kbps

VIDEO STANDARDS

H.261, H.263, H.263+

VIDEO FEATURES

Picture in Picture (PIP)

VIDEO INPUTS (1 INPUT)

Built-in main camera
1 x RCA / Phono, composite: document camera / auxiliary

VIDEO FORMAT

NTSC, PAL

LIVE VIDEO RESOLUTIONS

CIF (352 x 288 pixels)

AUDIO STANDARDS

G.711

AUDIO FEATURES

Automatic noise reduction
Acoustic echo canceller
Automatic gain control

PRIVACY FEATURE

Headset, 2.5 mm mini jack

FRAME RATES

15 frames per second 56 – 128 kbps
30 frames per second 168 – 768 kbps

NETWORK

Requires CallManager version 4.0 or newer
Network features as supported by Cisco SCCP and Cisco CallManager
Interoperability with H.323 and H.320 through Cisco CallManager

CALL CONTROL

Includes Cisco SCCP functions such as call waiting, call forwarding, call transfer to voice and video IP phones, call hold, call monitoring, call park, call back, call join, call pickup

WIRELESS LAN SUPPORT

Compliant with IEEE 802.11b, up to 11 Mbit
Support for 64 / 128 bit encryption (WEP)
Infrastructure or ad-hoc mode

ETHERNET / INTERNET / INTRANET CONNECTIVITY

TCP/IP, DHCP, ARP, FTP, Telnet, TFTP, DNS
Wired 10/100 Mbit full / half duplex (manual or auto detect selection)

CAMERA

1.7 x zoom
1/3" CCD
+5° / -20° tilt (mechanical)
47° vertical field of view
65° horizontal field of view
450 (PAL) / 460 (NTSC) horizontal TV lines
Min. illumination 0.5 Lux (F1.4)
Manual focus
Auto or manual brightness and white balance

DIRECTORY SERVICES

Missed calls list
Received calls list
Placed calls list
Shared and personal directory
Advanced directory search

POWER

Auto-sensing power supply
100 – 250 VAC, 50 – 60 Hz
45 watts max.

UNIT DIMENSIONS

Height: 17.7" / 45.0cm
Width: 11.8" / 30.0cm
Depth: 2.6" / 6.6cm
Weight: 9.0lbs / 4.1kg

All specifications subject to change without notice.



The TANDBERG 1000 for CallManager has been tested and confirmed by Cisco to fully interoperate in a CallManager 4 SCCP environment providing the same telephony features found on the Cisco 7960 phones. In addition, these products have been tested in Cisco's H.323 IP/VC environment and were found to be fully compliant with the Cisco IP/VX 35xx product family, Cisco MCM and Cisco Aironet 350 Wireless LAN adapter. For full disclaimer see TANDBERG product documentation or the following Web site: www.tandberg.net.

TANDBERG is a registered trademark or trademark of TANDBERG and/or its affiliates in the U.S. and certain other countries.

Cisco is a registered trademark of Cisco Systems, Inc. and/or its affiliates in the U.S. and certain other countries.

All other trademarks are property of their respective owners.

TANDBERG

1000

For Cisco® CallManager

TANDBERG WORLD HEADQUARTERS
Philip Pedersens vei 22
1366 Lysaker, Norway
Tel: +47 67 125 125
Fax: +47 67 125 234
Video: +47 67 117 777
E-mail: tandberg@tandberg.net

200 Park Avenue, Suite 2005
New York, NY U.S.A. 10166
Tel: +1 212 692 6500
Tel: +1 800 538 2884 (toll free in the U.S.)
Fax: +1 212 692 6501
Video: +1 212 692 6535
E-mail: tandberg@tandbergusa.com

June 2004